


- * Extensive operating voltage DC12 ~ 240V or AC24 ~ 240V.
- * High Capacity relay output 3A/250VAC.
- * High compact structure IP-65.
- * Multi Surge kicker circuit effectively protects from surge damage.
- * B Type (Normal close Type) have no stock maybe, accepted order to manufacture

Model : A3R-30XB 、 A3R-1MXB 、 A3R-2MXB 、 A3G-2MRB 、
A3G-4MXB 、 A3T-10MXB 、 A3T-20MXB

- * Polarity Mirror Reflexives (A3G-4MRE) Reflex Type available.



Type	Figure	Model	Sensitivity Adjuster	Sensible Distance	Guiding of Model
Reflex Type		A3R-30X	270° Trimmer	30 CM	Ex : A3 R- 30 XB- P ① ② ③ ④⑤ ⑥ ① SERIES A3 : Free Power Photo Sensor
		A3R-1MX		1 M	
		A3R-2MX		2 M	
		A3R-30XP		30 CM	
		A3R-1MXP		1 M	
		A3R-2MXP		2 M	
Mirror Reflex Type		A3G-2MR	Without	2 M	② Type R : Reflex Type G : Mirror Reflex Type T : Thru Beam Type ③ Sensing Distance 30=30cm 1M=1m 2M=2m 10M=10m
		A3G-2MRS		2 M	
		A3G-4MRE		4 M	
		A3G-4MX		4 M	
		A3G-2MRP	270° Trimmer	2 M	
		A3G-4MXP	Without	4 M	
		A3G-4MXP		4 M	
		A3G-4MXP		4 M	
A3G-4MXP	4 M				
Thru Beam Type		A3T-3MX	Without	3 M	④ Emitter X : Infrared LED. R : Red LED. ⑤ Output Status non : NO TYPE B : NC TYPE ⑥ Protection Class non : IP-65 P : IP-67
		A3T-10MX		10 M	
		A3T-20MX		20 M	
		A3T-3MXP		3 M	
		A3T-10MXP		10 M	
		A3T-20MXP		20 M	