


- * Extensive operating voltage DC12 ~ 240V or AC24 ~ 240V.
- * High Capacity relay output 3A/250VAC.
- * High compact structure IP-66
- * Multi-protection circuit—Burst test over 2KV.
- * Longer sensing distance
 - Thru beam type : 30m
 - Mirror reflex type : 8m



Type		Figure	Model	Sensitivity Adjuster	Sensible Distance		Guiding of Model
Reflex Type	Standard Type		E3R-60X	270° Trimmer	60 CM		Ex : <u>E3 R- 60 XB-</u> ① ② ③ ④ ⑤ ① SERIES E3 : Free Power Photo Sensor ② Type R : Reflex Type G : Mirror Reflex Type T : Thru Beam Type ③ Sensing Distance 30=30cm 1M=1m 10M=10m ④ Emitter X : Infrared LED. R : Red LED. ⑤ Output Status non : NO TYPE B : NC TYPE
			E3R-60XB				
	Timer Type		M3R-60X	Off delay 0~1sec adjustable	60 CM		
			M3R-60XB				
Mirror Reflex Type	Standard Type		E3G-8MX	Without	MR-1	8M	
			E3G-8MXB		MR-2	4M	
	Timer Type		M3G-8MX	With On delay 0~1sec adjustable	MR-3	12M	
			M3G-8MXB				
Polarity Mirror Reflexives	Standard Type		E3G-6MRE	Without	MR-1	6M	
			E3G-6MREB		MR-2	3M	
	Timer Type		M3G-6MRE	With On delay 0~1sec adjustable	MR-3	8M	
			M3G-6MREB				
Thru Beam Type	Standard Type		E3T-10MX	Without	10M		
			E3T-10MXB				
			E3T-30MX				
			E3T-30MXB				
	Timer Type		M3T-30MX	With On delay 0~1sec adjustable	30M		
			M3T-30MXB				

Note : 輸出狀態 <NC> Type 非經常性庫存，如果需要請預先訂購。