

240W Three Phase DIN Rail Power



- Input 340~550VAC, 3-phase 4 wires
- High efficiency and low dissipation
- Protections: Short circuit / Overload / Over voltage / Over temp.
- Installed on DIN rail TS35/7.5 or 15
- EN61000-6-2 industrial immunity level
- 100% full load burn-in test
- Approvals: UL / CUL / TUV / CB / CE
- Cooling by free air convection
- 3 years warranty

CASE: 922A 125.5x 125.2x 100 mm

AC input voltage range	340~550 VAC, 3-phase 4 wires (dual-phase operation possible)
AC inrush current	Cold start, 50A
DC adjustment range	24V: 24~28V, 48V: 48~55V
Overload protection	105%~150% constant current, auto-recovery
Over voltage protection	24V: 30~36V, 48V: 59~66V
Over temp. protection	Shut down output voltage, recovers automatically after temperature goes down
Withstand voltage	I/P-O/P: 3KVAC, I/P-FG: 1.5KVAC, 1 minute
Working temperature	-20 ~ +70°C (refer to output derating curve)
Safety standards	UL508, UL60950-1, TUV EN60950-1 approved
EMC standards	EN55022 class B, EN61000-3-2,3, ENV50204, EN61000-4-2,3,4,5,6,8,11, EN61000-6-2, EN61204-3
Connection	I/P: 4 poles, O/P: 4 poles screw DIN terminal
Packing	1.3kg ; 12pcs / 16.6kg / 1.34CUFT

Stock No.	Model No.	Output	Tol.	R&N	Effi.
10941	DRT-240-24	24V, 0~10A	±1%	80mV	89%
10942	DRT-240-48	48V, 0~5.0A	±1%	80mV	89%